

Italtex Wallmaster N6 covers an area of 5sam at a thickness of 6mm. The thickness allows textures to be etched onto the render & patterns cut to suit.

Designer effects are

or developer.

limited to the creativity and imagination of the architect, interior designer, contractor

ITALTEX

Italtex Wallmaster is a cement based wall coating used for both interior and exterior wall cladding. It can be applied as a troweled coat or textured to create designer effects thus providing a beautiful finish

A bag of Italtex Wallmaster N3 covers an area of 9-10sm² at a thickness of 3mm.

There are over 40 different colors available in hues of reds, greys, yellows & browns other shades can be manufactured on order.



High Point Deko is among the top companies specializing in normal paints, textured decorative finishes, construction and renovation works, We also offer professional paint application and interior design services.

SERVICES OFFERED INCLUDE

INTERIOR & EXTERIOR PAINTS







DECORATIVE PAINTS











Red Planet Centre, Ngong Road Phone: (254) 20 440 2952 Cell: (254) 792 959 754 oint Email: sales@highpointdeko.co.ke Url: www.highpointdeko.co.ke





25±0.2kg



About Us:

High Point Deko is a concrete solutions company & specializes in water proofing. It's the largest distributor of Italtex adhesive cement & grout.

We offer quality products & services our solutions are offered by experts and are widely appreciated for being reliable, timely & cost effective and trusted system solutions for every aspect of tiling our products are suitable for all kind of tiles indoor and outdoor, domestic & commercial projects.

ITALTEX BRAND is certified by Kebs, manufactured tested to the highest standards Assuring customers that product will perform to the required specifications.

The company is domiciled in Kenya and is headquarted at Red Planet Centre Ngong Road, Nairobi. We are also the manufacturers of Acrylic Based Paints.

VISION

TO BE THE MOST LIABLE & TRUSTED

SUPPLIER OF CONCRETE SOLUTIONS
WITH ADHESIVE CEMENT,
GROUT & BUILDING

SOLUTIONS MANUFACTURING

COMPANY IN AFRICA

OFFERING BROAD SPECTRUM

OF RELATED SERVICES

& PRODUCTS, COMMITTED

TO SERVICE EXCELLENCE

& RENOWNED FOR INTEGRITY

& ABILITY TO DELIVER









ITALTEX PREMIUM

Heavy duty adhesive perfect for porcelain granite big size tiles Swimming pool & other non porous tiles walls & floor tiles wall & floor tiles in interior & exterior installations.

CHARACTERISTICS:

- Extra Strong
- High Tensible Strength
- Flexible
- Fast & Easy Installation
- Professional Finish
- Economical
- Non Porous

ITALTEX SUPER (NORMAL)

Normal cementitious tile adhesive is ready mixed high strength cement based for fixing wall & floor tiles on to substrate of rendering & screed ceramic tiles.

THE PERFECT

ITALTEX GROUT

Italtex Grout is available in a range of colours & a convenient to use 3kg & 1kg bag.

Italtex Grout is used to fill the spaces between tiles and support them on the surface of installation.

Italtex Grout comes in various colors & shades, & it keeps your tile from expanding & shifting with the change in temperature & moisture level.

There are three traditional types of grout available for tile installation, as well as advanced formulas engineered for color consistency & durability. While you should always research a grout that caters to your specific project, the basic three types are cement, pre-mixed & epoxy.







FOR YOUR BUILDING SOLUTIONS

WATER PROOF POWDER

ITALTEX BASIC WATER PROOFING FOR POWDER COMPOUND FOR PLASTER & CONCRETE:

is used for water proofing of concrete & sand cement mortar used in basements roof slabs and screeds, water retaining structures, external plastering bathrooms & balconies.









ITALTEX SKIM COAT

Multipurpose skimcoat
Manufactured to provide
high quality smooth Surface
finish suitable for concrete
/cement plastered interior
& exterior surfaces of
rendering & screed



ITALTEX Gypsum filler is gypsum-based setting material for bulk & secondary filling of plaster-board joints. A low shrinkage product for hand application, with 60 minutes working time. It can be used in stages 1 & 2 of the traditional 3-stage jointing process.

ITALTEX Gypsum produce a smooth, continuous, crack-resistant lining surface ready for priming &final decoration. A number of jointing specifications are available to suit the board type, site preference & method of application. When taping & jointing, **ITALTEX Gypsum** is suitable for application of the taping coat only. It sets to a hard finish & is ideal for use on plasterboard joints under **ITALTEX Gypsum**, Suitable to fix cornices.





TO IMPROVE
& PROVIDE
OUTSTANDING
PRODUCTS
& MAINTAIN
EXCELLENT
CUSTOMER
RELATIONSHIPS

INTEGRITY
TRANSPARENCY
AFFORDABLE
TIMELY
EFFICIENCY

3